

Type 1100: Eye Link Belt / OGB Belt / OGB-L Belt

Features of the eyelink belt (OGB-L belt / OGB belt) :

- Straight running of the eye link conveyor belt
- Positive drive without creeping
- Large open area enables washing or drying of products on the eyelink belt
- When operated in a bath, it does not carry out the bath content
- Small contact surface with product, where necessary
- High rigidity and long lifetime of these eyelink conveyor belts
- Easy to clean, does not blind

Application of the eyelink conveyor belting :

As a bakingband and drying conveyorbelt in food industry, especially in bakery, confectionary and chocolate industry, freezerbelt, as an eyelink conveyor and washing belt in chemical and engineering industry, as a eye link cooling belt for rubber and plastic products, as a transport belt in wrapping machines for foiling, as a pasteurizer belt in tunnel pasteurizers, as an eyelinkbelt in a pizza tunneloven belt, tunnelfreezer belt in the fishindustry etc.

Technical data of the eye link conveyor belt (OGB-L belt / OGB-belt) :

Pitch of cross rods	20,00 • 100,00 mm
Mesh width	1,0 • 40,0mm
Diameter of cross wires	4,0 • 8,0 mm
Diameter of wire links	1,00 • 4,00 mm
Standard materials	bright steel • stainless steel
Operating temperature	below 400°C
Maximum beltwidth	6000 mm
Termination of edges	with weld (G) • nut (M)