

Type 1400: Honey-Flex Belt (STR) / Lotension Flat Wire Belt

Features of the lotension honeycomb spiral freezer / cooker conveyor belt :

- Straight run of the gridbelt
- Positive driving of the lotension radiusbelt without slipping
- Possible running of the lotension conveyor belt into a curve or a spiral
- Large open area allows easy air flow on the lotension freezer belt
- Long lifetime of the turn curve belt

Application of the freezer / cooking / cooling / gridbelt :

As a conveyor belt in freezing and cooling tunnels, as a conveyor belt in confectionery and chocolate industry, as a cooling belt in bakeries, a conveyor belt in the chemical industry, as a supporting belt in special driers, as a conveyor plotting belt in special discharging towers at ports and airports, pasteurizing belt, cooking belt, spiral freezerbelt, pizza conveyor belt etc.

Technical data of the lotension conveyor belting :

Pitch of cross rods	19,05 mm • 38,1 mm
Pitch of spiral wires	5,00 mm • 27,40 mm
Diameter of cross rods	4,9 mm • 6,0 mm
Diameter of flat wire	o.a. 9,5 x 1,2 mm • 10 x 1 mm • 13 x 2 mm
Standard materials	stainless steel • carbon steel
Working temperature	from -200 to +400°C
Edge ends	welded buttonhead